

TIPO TYPE		HP	GIRI R.p.m. Tours	Bocche Hoses Orifices	Adescam. Priming Amorçage (m)	Hmax (m)	PORTATA - CAPACITY DEBIT (LT/MIN)					
Monofase - 1 phase 230 V 50 Hz	Trifase - 3 phase 400 V 50 Hz						1 m	5 m	10 m	15 m	20 m	30 m
Art. 700 - ALM 20	Art. 710 - ALT 20	0.5	2800	3/4" M	6	24	28	23	17	11	5	
Art. 700 L - ALM 20 L	Art. 710 L - ALT 20 L	0.2	1400	3/4" M	6	6	11	2				
Art. 701 - ALM 25	Art. 711 - ALT 25	0.6	1400	1" M	6	12	43	28	8			
Art. 702 - ALM 30	Art. 712 - ALT 30	2	2800	1" M	6	42	89	80	70	59	48	26
Art. 704 - ALM 40	Art. 714 - ALT 40	1.2	1400	1"1/2 M	6	17	137	112	76	24		
Art. 705 - ALM 50		2	1400	2" M	6	29	205	176	140	104	69	
	Art. 715 - ALT 50	2.5	1400	2" M	6	29	205	176	140	104	69	

Caratteristiche riferite al funzionamento con acqua. Ci riserviamo la facoltà di apportare modifiche senza obbligo di preavviso / Performances referred to operation with water We reserve the right to make modifications without prior notice / Caracteristiques référées au fonctionnement avec eau. Sous réserve de modifications sans avis préalable